



Key Features

- Extremely affordable single frequency, multi constellation solution with up to 20 Hz update rate
- GPS, GLONASS, BeiDou, Galileo, and QZSS-ready
- Fast start-up and reacquisition times allow you to get right to work
- High-precision, differential positioning accuracy of 60 cm, 95% of the time
- Exclusive e-Dif® option where other differential signals are not practical
- COAST and SureTrack maintain sub-meter DGNSS positioning for 40 minutes after correction loss
- Small form and low-power consumption design is ideal for easy integration

Hemisphere GNSS' Crescent P206 and P207 OEM modules use GPS, GLONASS, and BeiDou, and are Galileo and QZSS ready. Track more signals for unparalleled positioning performance even in challenging environments. Leverage the compact size and easy integration in your design. The 34-pin P206 module is a drop-in upgrade for many Hemisphere products. P207 is a drop in upgrade for existing Crescent designs using standard 20 pin modules from other manufacturers.

DGPS and SBAS with patented COAST™ software enables Hemisphere receivers to use previous DGPS and SBAS correction data during times of interference, signal blockage and weak signal. The receiver will coast and continue to maintain sub-meter positioning for up to 40 minutes without any DGPS signal. When your corrections are only for one GNSS constellation, for example GPS using SBAS, Hemisphere's patented SureTrack™ goes to work to model all other satellites, helping maintain an accurate solution in challenging environments.

GNSS Receiver Specifications

Receiver Type:	GNSS single-frequency RTK with carrier phase
Signals Received:	GPS, GLONASS, BeiDou, GALILEO ¹ , and QZSS ¹
Channels:	103
GPS Sensitivity:	-142 dBm
SBAS Tracking:	3-channel, parallel tracking
Update Rate:	1 Hz standard, 10 or 20 Hz optional
Timing (1 PPS)	
Accuracy:	20 ns
Cold Start:	< 60 s typical (all unknown)
Warm Start:	< 30 s typical (no ephemeris)
Hot Start:	< 10 s typical (all known)
HeadStart: ⁵	Removable, auto-recharging onboard clock battery
Maximum Speed:	1,850 mph (999 kts)
Maximum Altitude:	18,288 m (60,000 ft)

Accuracy

Positioning:	RMS (67%)	2DRMS (95%)
Autonomous, no SA: ³	1.2 m	2.5 m
SBAS: ³	0.3 m	0.6 m
RTK: ²	10 mm + 1 ppm	20 mm + 2 ppm

Communications

Ports:	4x full-duplex 3.3 V CMOS (3 main serial ports 1x differential-only port) 1x USB Host ⁶ 1x USB Device
Baud Rates:	4800 - 115200
Correction I/O Protocol:	Hemisphere GNSS proprietary ROX format, RTCM v2.3, RTCM v3.2, CMR ⁸ , CMR+ ⁸
Data I/O Protocol:	NMEA 0183, Crescent binary ⁷
Timing Output:	1 PPS, CMOS, active high, rising edge sync, 10 k Ω , 10 pF load
Event Marker Input:	CMOS, active low, falling edge sync, 10 k Ω , 10 pF load

Power

Input Voltage:	3.3 VDC +/- 5%
Power Consumption:	1.2 W nominal L1 GPS 1.4 W nominal single frequency GPS + GLONASS + BeiDou
Current Consumption:	0.30 A nominal GPS (L1) 370 mA nominal L1 GPS 420 mA nominal single frequency GPS + GLONASS + BeiDou
Antenna Voltage:	15 VDC maximum Antenna Short Circuit
Antenna Short Circuit Protection:	Yes
Antenna Gain Input Range:	10 to 40 dB
Antenna Input Impedance:	50 Ω

Environmental

Operating Temperature:	-40°C to +85°C (-40°F to +185°F)
Storage Temperature:	-40°C to +85°C (-40°F to +185°F)
Humidity:	95% non-condensing (when in an enclosure)

Mechanical

Dimensions:	7.25 L x 4.1 W x 1.1 H (cm) 2.85 L x 1.61 W x 0.43 H (in)
Weight:	.105 kg (3.70 oz.)
Status Indications (LED):	Power, Primary and Secondary GPS lock, Differential lock, DGPS position, Heading, RTK lock, Atlas L-band lock
Power/Data Connector:	
P206:	34-pin male header 0.05" pitch
P207:	20-pin male header 0.05" pitch
Antenna Connectors:	MCX, female, straight

1. Firmware update required
2. Depends on multipath environment, number of satellites in view, satellite geometry baseline length (up to 10 km) and ionospheric activity
3. Depends on multipath environment, number of satellites in view, satellite geometry and ionospheric activity
4. Cold start means no approx. position, no approx. time, no almanac, no ephemeris - Warm starts require an approx. position, approx. time, and almanac - Hot starts require an approx. position, approx. time, and valid ephemeris
5. Maintains time while receiver is powered off, reducing cold start occurrences
6. P206 Only
7. Hemisphere GNSS proprietary
8. CMR and CMR+ do not cover proprietary messages outside of the typical standard



Hemisphere GNSS

8515 E. Anderson Drive
Scottsdale, AZ 85255, USA

Phone: +1 (480) 348-6380
Toll-Free: +1 (855) 203-1770
Fax: +1 (480) 270-5070

precision@hgns.com
www.hgns.com